

UTIFORM Quattro

Continuous Mixing Grouting System

Narrow enough to easily roll through doorways, the Quattro is ideal for both spray and pour applications.

ChemGrout's UF Quattro

System features:

- Built-in air compressor
- All electric power
- Precision water control
- 8 full bag hopper capacity
- 5 to 13 gpm
- Pressures up to 450 psi
- Pumping distance up to 130'
height up to 66'
(based on materials)



The versatile Quattro sprays mortars as well as pumps self-leveling underlayments.

NEW from ChemGrout®

- Portable
- Easy to use
- Versatile

Complete self-contained unit ideal for:

- EIFS
- Fireproofing
- Stucco
- Plaster
- Self-leveling underlayments
- Mortar sprayer

ChemGrout®

Widest Selection of Grouting Equipment in the World

UTIFORM Quattro

Self-contained, with built in air compressor and water pump, the Quattro delivers a non-stop, steady material flow for a variety of spray and pour applications. Dry materials are conveyed from the hopper via a metering star wheel into the mixing chamber. Precision water controls ensure that the proper amount of water is added. The benefits of a single operator, superior material consistency and flow rates of up to 13 gpm, translates into big savings in both time and money. Control boxes are hermetically sealed to protect them from dust and water. Automatic shutoff systems, remote control, extra rotor/stator, grout/air hoses, spray wand, hopper cover and tool kit are standard. Optional pneumatic silo conveyor is available.

**Complete System includes:
Machine, 100' grout and
air hose, spare rotor/stator,
spray wand and tool kit.**

Large hopper
holds 8 full
bags

Built in air
compressor
for spraying,
mortar, stucco
& fireproofing

**Flow rates:
5 to 13 gpm
Pressures:
to 450 psi**



Requires
440 V,
3 phase,
20 amps

Sturdy,
lightweight
chassis

Accurate
water
control
system

Sealed
control box

Large wheels
with locks

Specifications

Maximum output	5 to 13 gpm	Air compressor	8.8 CFM, 72psi, 1.2HP
Pumping distance	130 ft.	Water pressure required	42psi
Pumping height	66 ft.	Electrical connection	440 V, 60Hz, 3 phase, 20 amps
Pumping pressure	450 psi	Size	44"L x 26"W x 58"H
Power of mixing motor	7.5 HP	Weight	408 lbs.
Power of feed motor	1.0 HP	Loading height	34"

ChemGrout®

Widest Selection of Grouting Equipment in the World

ChemGrout, Inc., P.O. Box 1140, 805 E. 31st Street, LaGrange Park, IL 60526 USA

Phone: (708) 354-7112 • Fax: (708) 354-3881

Visit our web site: www.chemgrout.com • E-mail: info@chemgrout.com



High outputs and a consistent discharge provide a perfect fit for pumping self-leveling underlayments.



Convenient height for loading, hopper holds 8 full bags!



Durable hopper cover protects against contamination and doubles as dust shield.



Built-in handles for lifting by two people allows for easy movement.



Unit disassembles in minutes for easy transportation.